



## Gaia™ 100

LEO/MEO satellite tracking ground stations for  
business and mission-critical applications



## Gaia 100 Key Features

— No “key hole”, for uninterrupted horizon-to-horizon tracking

— Real 3-axis system – EL, Tilt and AZ – for greater availability and reliability

— Built-in, step-track-based Advanced Control Loop™, for superior performance

— Innovative GaiaLink™ software, for ease of integration and operation

— Radome covered, for anytime/anywhere operation

— Multiple configurations (from L- to K-band) in a single platform

— Mature product with multiple installations around the globe

— Short lead time

## Make Your Data Count - Every Time

Earth Observation (EO) has become an essential part of our daily lives. The earth is constantly monitored, analyzed and measured by governmental agencies, defense forces and the private sector. From weather forecasting to disaster control, for oil and gas exploration and resource monitoring, earth observation data is vital to a growing body of applications that profoundly affects all of us.

New and growing constellations of Low Earth Orbit (LEO) and Medium Earth Orbit (MEO) satellites continuously circle our globe, providing visible imaging, radar screening and spectral analysis of our planet, as well as new communications services. To access data captured by these satellites, a fast and reliable communications link must be established between the moving satellites and the earth. Communication can only be established when there is a line of sight between the satellite and the ground station. For LEO satellites, this communications “time window” typically lasts only a few minutes, so the goal is to get the most out of it.

Important decisions depend on the reliability of such communications links and there are no second chances. Orbit’s LEO/MEO ground station solution for business- and mission-critical applications was designed to help ensure you never lose crucial data or connectivity.

## Gaia 100 family

Rethinking Ground Stations for EO and New Space

Combining years of experience and an extensive installed base with lessons from the emerging New Space sector, Orbit is rethinking traditional ground stations – making them more compact and cost-effective – to address the dynamic needs of its EO

The Gaia 100 family is available in 4 antenna sizes:



Gaia 100 2.4 m



Gaia 100 3.7 m



Gaia 100 4.5 m



Gaia 100 5.5 m

and constellation customers. The company's Gaia 100 family comprises cost-effective, high-performance terrestrial terminals for proven and reliable connectivity with LEO/MEO satellites.

## Tracking Superiority

The combination of Orbit's Advanced Control Loop™ algorithm and integrated RF tracking meets the demanding accuracy requirements of the Ka-band frequency range, ensuring that your ground station is ready for current and next-generation satellites.

Gaia's boresight pointing capability (the ability to pinpoint the center of a moving target) ensures maximum peak (G/T) reception performance while tracking the satellite, optimizing link performance and margins.

Gaia 100 can also be configured with a dual S-/X-band feed that supports simultaneous or switchable RHCP and LHCP polarization. It typically uses X-band for downloading data from the satellite and S-band for the control and monitor management channel in both receive and transmit modes.

A single band feed is also available (in S- or X-band configurations). All antennas are designed to ensure continuous operation even when the LEO tracking path is at its zenith.

All Gaia ground stations come equipped with a ruggedized radome that enables them to withstand even the harshest environmental conditions.

## Monitoring and Control

Gaia earth stations employ an intuitive, user-friendly GaiaLink™ interface for overall management of system operations. The controller allocates antenna resources while managing constellation tracking of the LEO, MEO and GEO satellites.

## GaiaLink Software Key Features

- Ability to monitor and control one or many ground stations at once
- Advanced graphical user interface
- Secured SCP for host antenna file transfer (TLE, routing, scheduling, SW upgrades)
- Scheduler option for automatic "send & forget" antenna action plan
- Colored indicators for AGC signal levels
- SDK for easy user program interface
- Easy and intuitive configurable desktop
- User-defined multiple views
- Advanced antenna log limited only by disk space

## The Gaia Family Advantage

Gaia is field proven on over 50 systems installed around the world. A mature, low-load design and heritage Field Replaceable Units (FRUs) and software are common to the entire Gaia family, ensuring high reliability, spares commonality, ease of maintenance and reduced lifecycle costs of ownership across a site or network.

## World-Class Customer Support

Through our International Service Centers, Orbit's trained support engineers are available 24/7 to handle the urgent needs of customers worldwide. A global inventory replenishment system ensures efficient spare parts distribution across regions. With the capability to remotely access systems for troubleshooting and diagnostics, Orbit's real-time service support increases availability for enhanced customer satisfaction and cost benefits.

## Applications

Orbit's globally installed tracking systems operate under extreme environmental conditions to meet the needs of a broad range of challenging applications, including:



Gateways and  
TT&C for MEO/LEO  
constellations



Weather  
forecasting



Disaster  
monitoring and  
control



Search and  
rescue  
missions



Surveillance  
for military and  
homeland security



Oil & gas  
exploration



Land  
mapping



# Gaia 100 System Specifications

	Gaia 100 2.4 m	Gaia 100 3.7 m	Gaia 100 4.5 m	Gaia 100 5.5 m
Antenna Diameter	2.4 m (7.9 ft)	3.7 m (12.1 ft)	4.5 m (14.7 ft)	5.5 m (16.4 ft)
Frequency Range	S-Band Transmit: 2020-2120 MHz S-Band Receive: 2200-2300 MHz X -Band Receive: 7900-8400 MHz Optional X-Band (7700 – 8500 MHz) Optional S-Band (2400-2500 MHz)			
G/T (including radome loss)	S-Band: 9 [dB/°K]; X-Band: 21.5 [dB/°K]	S-Band: 12.8 [dB/°K]; X-Band: 25.4 [dB/°K]	S-Band: 14.5 [dB/°K]; X-Band: 27.1 [dB/°K]	S-Band: 16.2 [dB/°K]; X-Band: 30 [dB/°K]
Environmental Conditions				
Wind Operational/Survival	Up to 185 Km/hour (115 miles/hour)			
Temperature Range	Operational: -25°C to +55°C (-13°F to +130°F), (-40°C/-40°F optional) Storage: -40°C to +70°C (-40°F to +158°F)			
Altitude	Operational: 6,300 meter (20,000 ft) Transportation: 12,600 meter (40,000 ft)			
Rain	IP rating X6 (radome enclosed)			
Mechanical Specifications				
Max Velocity	20°/sec	10°/sec	5°/sec	5°/sec
Max Acceleration	10°/sec <sup>2</sup>	5°/sec <sup>2</sup>	5°/sec <sup>2</sup>	5°/sec <sup>2</sup>
Weight (Including Radome)	850 Kg (1874 lb)	1500 Kg (3307 lb)	1900 Kg (4189 lb)	2500 Kg (5512 lb)
3 Axis	Az: Continuous rotation / Elevation: 0-90° / Tilt: ±30°			
Radome Dimensions				
Base Diameter	4.0 m	4.9 m	6.4 m	7.0 m
Height	3.6 m	4.6 m	5.6 m	6.6 m
Power Input	90-130VAC or 200-250VAC 50/60Hz			
Safety	EN 60204-1, ISO 12100-2, EN 614-1, IEC 60945:2002			

## How to order:



Gaia 100

Dish Size

Band Type

## Band types (partial configuration table)

S&X Full Simultaneous	X-band Manual
S&X Full Switchable	X-band Switchable
X RHCP/LHCP S Switchable	Ka-band RHCP or LHCP
L&S Switchable	S-band Switchable
S&X Manual	X-band RHCP Only
Ka-band Switchable	X-band LHCP Only

\* Additional configurations are available. For more information, visit [www.orbit-cs.com](http://www.orbit-cs.com).